



# OneStream G

## Product Information



TelecomFM's OneStream G represents a new approach in corporate mobile & VoIP convergence. OneStream G is designed to convert outgoing and incoming calls from VoIP to mobile, thus enabling end customers to take advantage of cost savings.

The OneStream G provides the following interfaces:

Wireless (GSM 850, 900, 1800, 1900)

Packet (SIP)

OneStream G can be used to intelligently route calls between these media efficiently and in a scalable fashion thereby producing cost effective communication for any size of business.



Dealer's Stamp

... a global vision of customer interconnection

---

GSM Module	2 x Siemens MC55 / MC56
Bands	GSM 850MHz GSM 900MHz GSM 1800MHz GSM 1900MHz
Transmit Power	Class 4 (2W) for EGSM 850MHz Class 4 (2W) for EGSM 900MHz Class 1 (1W) for GSM 1800MHz Class 1 (1W) for GSM 1900MHz
Speech Codecs	Half Rate (HR) Full Rate (FR) Enhanced Full Rate (EFR) Adaptive Multi-Rate (AMR)
GSM Antennae	2 x Gold plated SMA Male Connectors for remote antennae (included)
SIM Card	2 x 3V Small card

---

## VoIP Interface

Channels	6 IP Channels
Physical	10/100M Autosensing RJ45 Ethernet port
Signalling	SIP (Session Initiation Protocol)
Voice Codecs	G.729, G.711u, G.711a
Protocols	TCP, UDP, SIP, RTP HTTP, FTP, DHCP

---

